

Administrator, Telephone
CLO Martin Mansnerus, +46104785322

Date 2026-08-10

Version: 2
Reg.No:

Guidelines and Restrictions – Port of Slite (SESLI)

Purpose

To be used by pilots, port authorities, ship owners, charterers, cargo owners, ship agents or other stakeholders for guidance about limitations and restrictions in the port of Slite.

General information

If no deficiencies have been reported when ordering pilot, the vessel must be suitably ballasted so that propeller, rudder and any bow- and/or stern thrusters operates with optimum efficiency. If not, due to safety reasons, the pilot has the right to postpone the arrival/departure until this has been corrected.

Pilot boarding position

- Slite (1,1nm/ South Magö) N 57° 39,5 E 018° 50,4

Communication and Reports

- There is no Port control. A general call on VHF Ch. 16 should be made before arrival and departure.
- Communication with Pilot Dispatch Center and pilot boat, VHF Ch. 10
- Linesmen work on VHF Ch. 12
- Tugboats work on VHF Ch. 08

Linesmen

- Ships agent or captain of the vessel orders linesmen separately in advance.

Fairway information

Fairway to/from Slite							
Port	Distance from pilot boarding	Fairway depth relative to RH 2000 (BSCD)	Max Fairway draft relative to RH 2000				Remark
Slite	3,3 nm	7,6m	6,9m				

Date 2026-08-10

Anchorage and use of anchor inside port

- **Anchorage areas:**
 - Slite Inner N 57° 38,0 E 018° 51,5
 - Slite Outer N 57° 36,0 E 018° 57,5
- **Unsuitable areas:**
 - Close to fairway line
- **Prohibited areas:**
 - Normally not applicable
- **Use of anchor inside port:**
 - Only in emergency

Berth information and maximum dimensions

Slite								
Berth	Cargo	Direction	Length (m)	Max Loa (m)	Max Boa (m)	Depth(m) Referens RH 2000	Max draft (m) Referens RH 2000	Remarks
Silo Pier/ Oil Jetty	Oil	083° / 263°	100m	100m	N/A	7,2m	6,7m	*On arrival to Silo pier/Oil jetty the Cement berth North must be free
Cementkaj/ North	Cement	109° / 289°	140m	130m	N/A	7,7m	6,9m	*On arrival Cement berth North, Silo pier /Oil jetty must be free
Cementkaj South	Cement	109° / 289°	130m	130m	N/A	7,7m	6,9m	.
Oceankaj	Bulk	173° / 353°	250m	160m	N/A	7,0m	6,5m	Vessel exceeding 160 meters LOA are requested to present vessels data concerning maneuverability 48 hrs prior to arrival for evaluation and approval from pilot area
Apotekskaj/ North	Bulk/ Cruise	087° / 267°	150m	140m	N/A	7,8m	6,9m	
Apotekskaj/ South	Bulk/ Cruise	087° / 267°	125m	100m	N/A	7,4m	6,9m	
Krokiga-kajen		013°/193°	110m	50m	N/A	4,8m	4,3m	

- Depth and draft at +/- 0 water level RH 2000 (BSCD), referens RH 2000 in Viva or local WL gauges

Date 2026-08-10

Tugboat information and requirements

- See guidelines below. The following are general guidelines.
 - The Pilot has the right, after consultation with the captain of the vessel, to require tugboats if deemed necessary.
 - *When a tugboat is ordered or will be used report to pilot area at least 24 hrs. in advance*
 - *When and if a conventional tugboat is used the swell must not exceed 2 m.*
-
- **Escort tug requirements**
 - Normally not applicable

 - **Bollard pull/Safe working load requirements - SWL (bollards and fairleads)**
 - No specific requirements, but vessel to have sufficient SWL for the current operation concerning weather and loading conditions

 - **Local tugboat and requirements**

Vessel arriving/departing have to comply with these requirements for safe maneuvering of the vessel in wind conditions up to 15 m/s. Restriction is divided in four steps (see below, Bow thruster power requirements), by length over all and sets the request of bow thruster power depending on the vessels actual draught. Wind conditions exceeding 15 m/s need tug assistance.

Vessels not meeting the minimum requirements stipulated is requested to present data concerning maneuverability not later than 24h prior to arrival for evaluation.

Bow thruster power requirements

Step 1

Length over all 70m up to 89m shall be equipped with a bow thruster power of min 35Hp/ meter actual draught (Dm)

Step 2

Length over all 90m up to 114m shall be equipped with a bow thruster power of min 60Hp/meter actual draught (Dm)

Step 3

Length over all 115m up to 134m shall be equipped with a bow thruster power of min 80Hp/meter actual draught (Dm)

Step 4

Length over all 135m and greater up to max allowed length over all in port shall be equipped with a bow thruster power of min 100Hp/ meter actual draught(Dm)

For tug with tow, pusher and barges see table below

Date 2026-08-10

Number of tugs – Standard for all Gotland ports						
Loa (m)	No bowthruster or bowthruster power <100 hp /m draught	Bowthruster with power 100 hp /m draught and wind > 15m/s				
>135	Minimum 1*	Minimum 1				
Note: Bow thrusters shall be in accordance with the minimum bow thruster requirements and must be capable of operating at full capacity for a period of not less than 30 minutes * Vessels not meeting the minimum requirements stipulated is requested to present data concerning maneuverability not later than 24h prior to arrival for evaluation						

Number of tugs – Standard for Gotland ports						
Loa (m)	Tug with tow	Pusher barges without bow thruster	Pusher barges with bow thruster must be able to maneuver in wind force up to 10 m/s			
N/A	1	1	1			
Note: Bow thrusters shall be in accordance with the minimum bow thruster requirements and must be capable of operating at full capacity for a period of not less than 30 minutes						

Date 2026-08-10

Visibility restrictions

- Normally no restrictions

Daylight restrictions

- Normally no restrictions

Wind restrictions

- Normally no restrictions

Source: According to Viva station Slite

Wave and swell restrictions

- Normally no restrictions
- When and if a conventional tugboat is used the swell must not exceed 2 m

Current restrictions

- Normally no restrictions

Two man pilotage

- Normally not applicable

Ice restrictions

- According to www.sjofartsverket.se/winternavigation.

Other restrictions

- For vessels not covered in this guidelines and restrictions e.g. tug and barges, special restrictions may apply. Vessels representative are requested to present data concerning maneuverability 48 hrs. prior to arrival for evaluation.
- On arrival to Silo pier/Oil jetty the Cement berth North must be free
- On arrival Cement berth North, the Silo pier /Oil jetty must be free